











PRODUCT OVERVIEW

Product	Item no.	Name	IP density	Power connection	Power consumption	Light spread	Lumen	Kelvin	LED quantity	RA value	Fastening holes	Hole pitch	Cable length	Length
	50530025	ALPHA	IP30	AC/DC 24V	5 W	45°	320 Lm	4.000-4.500	1 pcs.	>80	4 × M6	45 × 45 mm	1.8 m (no plug)	455 mm
	50530040	ALPHA	IP30	AC 100V-240V	5 W	45°	320 Lm	4.000-4.500	1 pcs.	>70	4 × M6	45 × 45 mm	2.0 m (incl. EU plug)	455 mm
	50530055	BRAVO	IP65	AC/DC 24V	4.5 W	60°	320 Lm	4.000-4.500	3 pcs.	>70	4 × M6	47 × 47 mm	2.0 m (no plug)	530 mm
	50530070	BRAVO	IP65	AC 100V-240V	4.5 W	60°	320 Lm	4.000-4.500	3 pcs.	>70	4 × M6	47 × 47 mm	2.0 m (incl. EU plug)	530 mm
	50531210	DELTA	IP20	AC/DC 24V	6 W	30°	510 Lm	5.700	3 pcs.	>80	4 × M4	60 × 60 mm	1.8 m (no plug)	455 mm
	50531220	DELTA	IP20	AC 100V-240V	3 W	30°	510 Lm	5.700	3 pcs.	>80	4 × M4	60 × 60 mm	1.8 m (incl. EU plug)	455 mm
	50531310	ECHO	IP65	AC/DC 24V	3 W	40°	220 Lm	5.700	1 pcs.	>80	4 × M4	50 × 50 mm	1.8 m (no plug)	500 mm
	50531320	ECHO	IP65	AC 100V-240V	6 W	40°	220 Lm	5.700	1 pcs.	>80	4 × M4	50 × 50 mm	1.8 m (incl. EU plug)	500 mm
	50531410	HELA	IP65	AC/DC 24V	6 W	30°	510 Lm	5.700	3 pcs.	>80	4 × M4	60 × 60 mm	1.8 m (no plug)	500 mm
	50531420	HELA	IP65	AC 100V-240V	6 W	30°	510 Lm	5.700	3 pcs.	>80	4 × M4	60 × 60 mm	1.8 m (incl. EU plug)	500 mm
	50530110	LEO	IP65	AC/DC 24V	9.5 W	45°	830 Lm	4.000-4.500	8 pcs.	>70	4 × M6	45 × 45 mm	2.0 m (no plug)	Total height: 280 mm
	50530120	LEO	IP65	AC 100V-240V	9.5 W	45°	830 Lm	4.000-4.500	8 pcs.	>70	4 × M6	45 × 45 mm	2.0 m (incl. EU plug)	Total height: 280 mm
	50530230	LYRA	IP65	AC/DC 24V	9.5 W	45°	830 Lm	4.000-4.500	8 pcs.	>70	4 × M6	45 × 45 mm	2.0 m (no plug)	190 × 270 mm
	50530240	LYRA	IP65	AC 100V-240V	9.5 W	45°	830 Lm	4.000-4.500	8 pcs.	>70	4 × M6	45 × 45 mm	2.0 m (incl. EU plug)	190 × 270 mm
	50530255	LIMA	IP65	AC/DC 24V	9.5 W	45°	830 Lm	4.000-4.500	8 pcs.	>70	4 × M6	45 × 45 mm	2.0 m (no plug)	400 × 400 mm
	50530265	LIMA	IP65	AC 100V-240V	9.5 W	45°	830 Lm	4.000-4.500	8 pcs.	>70	4 × M6	45 × 45 mm	2.0 m (incl. EU plug)	400 × 400 mm
	50531430	VELA	IP65	AC/DC 24V	6 W	30°	510 Lm	5.700	3 pcs.	>80	4 × M4	60 × 60 mm	1.8 m (no plug)	400 × 400 mm
	50531440	VELA	IP65	AC 100V-240V	6 W	30°	510 Lm	5.700	3 pcs.	>80	4 × M4	60 × 60 mm	1.8 m (incl. EU plug)	400 × 400 mm
	50531470	HYDRA Y alu base	IP65	AC/DC 24V	12 W	60°	1.020 Lm	5.700	6 pcs.	>80	4 × M4	45 × 45 mm	1.8 m (no plug)	400 × 400 mm
	50531485	HYDRA X plastic base	IP65	AC 100V-240V	12 W	60°	1.020 Lm	5.700	6 pcs.	>80	4 × M4	60 × 60 mm	1.8 m (incl. EU plug)	400 × 400 mm

RA VALUE

The RA value indicates how well the light reflects colour. Daylight has an RA value of 100, an incandescent light bulb has 99. The RA value of LED bulbs is typically between 80 and 97.

LUMEN

Lumen refers to the amount of light a bulb gives off. If you need to use something that is equivalent to the old 40-Watt light bulb, you should choose a bulb that emits 470 lumen.














KELVIN

A warm light has 2400-2900 Kelvin, which is equivalent to an incandescent light bulb. The higher the number, the whiter and more bluish the light appears. The lower the number, the more red and yellow is in the colour of the light. LED = 2000 to 8000K.

FIND THE RIGHT LED BULB



PRODUCT OVERVIEW

Product	Item no.	Name	IP density	Power connection	Power consumption	Light spread	Lumen	Kelvin	LED quantity	RA value	Fastening holes	Hole pitch	Cable length	Length
	50531525	NOVA	IP50	AC 100V-240V	14 W	120°	1.870 Lm	5.700 Dimmable 10-100%	-	>80	4 × M4	60 × 60 mm	1.8 m cable with plug and table mount	700 mm flex. arm
	50531500	NORD	IP50	AC 100V-240V	14 W	120°	1.820 Lm	5.700 Dimmable 10-100%	-	>80	4 × M4	60 × 60 mm	1.8 m cable with plug and table mount	400 × 400 mm
	50531610	FOXTROT	IP50	AC 100V-240V	14 W	120°	1.440 Lm	5.700	-	>80	4 × M6	45 × 45 mm	1.8 m (incl. EU plug)	400 × 430 mm
	50531625	X-RAY	IP50	AC 100V-240V	28 W	120°	2.880 Lm	5.700	-	>80	4 × M6	45 × 45 mm	1.8 m (incl. EU plug)	400 × 430 mm
	50530325	QUEBEC	IP65	AC/DC 24V	12 W	120°	1.080 Lm	4.000-4.500	-	>80	4 × M6	37-47 mm	2.0 m (no plug)	400 mm
	50530340	QUEBEC	IP65	AC 100V-240V	16 W	120°	1.080 Lm	4.000-4.500	-	>80	4 × M6	37-47 mm	2.0 m (incl. EU plug)	400 mm
	50530355	QUEBEC	IP65	AC/DC 24V	16 W	120°	1.440 Lm	4.000-4.500	-	>80	4 × M6	37-47 mm	2.0 m (no plug)	600 mm
	50530370	QUEBEC	IP65	AC 100V-240V	16 W	120°	1.440 Lm	4.000-4.500	-	>80	4 × M6	37-47 mm	2.0 m (incl. EU plug)	600 mm
	50530420	ORION	IP65	AC/DC 24V	8 W	60°	635 Lm	4.000-4.500	8 pcs.	>80	4 × M4	255-265 mm	1.0 m (no EU plug)	280 mm
	50530465	ORION	IP65	AC/DC 24V	20 W	60°	1.500 Lm	4.000-4.500	18 pcs.	>80	4 × M4	555-565 mm	1.0 m (no EU plug)	580 mm
	50532710	VEGA	IP67	DC 24V	14 W	120°	1.870 Lm	5.700	-	>80	4 × M6	25 mm	1.8 m (no plug)	350 mm
	50532720	VEGA	IP67	DC 24V	28 W	120°	3.740 Lm	5.700	-	>80	4 × M6	25 mm	1.8 m (no plug)	640 mm
	50532730	VEGA	IP67	DC 24V	42 W	120°	5.610 Lm	5.700	-	>80	4 × M6	25 mm	1.8 m (no plug)	930 mm
	50532610	VICTOR	IP67	AC/DC 24V	24 W	80°	2.040 Lm	5.700	12 pcs.	>80	4 × M6	35 mm	1.8 m (no plug)	515 mm
	50532620	VICTOR	IP67	AC 100V-240V	24 W	80°	2.040 Lm	5.700	12 pcs.	>80	4 × M6	35 mm	1.8 m (incl. EU plug)	515 mm
	50532630	VICTOR	IP67	AC/DC 24V	40 W	80°	3.040 Lm	5.700	20 pcs.	>80	4 × M6	35 mm	1.8 m (no plug)	870 mm
	50532640	VICTOR	IP67	AC 100V-240V	40 W	80°	3.040 Lm	5.700	20 pcs.	>80	4 × M6	35 mm	1.8 m (incl. EU plug)	870 mm

FIND THE RIGHT LED BULB



RA VALUE

The RA value indicates how well the light reflects colour. Daylight has an RA value of 100, an incandescent light bulb has 99. The RA value of LED bulbs is typically between 80 and 97.

LUMEN

Lumen refers to the amount of light a bulb gives off. If you need to use something that is equivalent to the old 40-Watt light bulb, you should choose a bulb that emits 470 lumen.

KELVIN

A warm light has 2400-2900 Kelvin, which is equivalent to an incandescent light bulb. The higher the number, the whiter and more bluish the light appears. The lower the number, the more red and yellow is in the colour of the light. LED = 2000 to 8000K.